


## Fig. 401M (Flanged) Cast Iron HNH-Milliken Plug Valves - Regular Pattern, Full Bore


### FEATURES AND BENEFITS

- Sealing compound effects a completely leak tight seal.
- When open - presents a straight through passage in line with pipeline
- Stops flow after 90° turn

### DIMENSIONAL DRAWINGS



401M - Sizes 2" to 4"



401MG - Sizes 5" to 6"

### DIMENSIONS AND WEIGHTS

#### Dimensions 401M

Nom Size	mm in	15	20	25	32	40	50	65	80	100
		1/2	3/4	1	1 1/4	1 1/2	2	2 1/2	3	4
A (401M)	mm	-	-	-	-	-	216	241	283	305
	in	-	-	-	-	-	8 1/2	9 1/2	11 1/8	12
B	mm	102	105	108	124	127	187	206	254	270
D Flanged ANSI 250	in	-	-	4 7/8	5 1/4	6 1/8	6 1/2	7 1/2	8 1/4	10
Wrench		G	G	G	J	J	L	L	O	P
Weight (401M)	kg	3.0	3.7	5.0	5.6	7.0	15	17	28	51

#### Dimensions 401MG (with gear unit)

Nom Size	mm in	125	150
		5	6
A	mm	381	403
	in	15	15 7/8
B	mm	381	473
D Flanged ANSI 250	in	11	12 1/2
Weight	kg	92	120

Every effort has been made to ensure that the information contained in this publication is accurate at the time of publishing. Hattersley Ltd assumes no responsibility or liability for typographical errors or omissions or for any misinterpretation of the information within the publication and reserves the right to change without notice.