

Fixed Orifice Double Regulating Valve (FODRV) MotoBalance S1832/S1832M/S1832L

FEATURES & BENEFITS

- Designed for installation in circuits where combined functions of actuated regulation and flow measurement are required.
- Easy to adjust/set flow using graduated dial and setting key.
- Tamperproof- once flow is set with key, it cannot be adjusted without key.
- The DN15 valve is also available in medium flow (S1832M) and low flow (S1832L). Dials are colour coded for easy identification:
 - S1832 - Standard Flow - White - 0.061 to 0.132 l/s
 - S1832M - Medium Flow - Yellow - 0.03 to 0.07 l/s
 - S1832L - Low Flow - Green - 0.016 to 0.04 l/s
- P84 test points fitted enable accuracy of flow measurement of +/- 5% across all drive settings.
- Profiled disc gives equal percentage flow control.
- Y-pattern globe valve.
- Integral square edged entrance orifice plates.
- Double regulating feature allows the valve to be used for isolation and to be re-opened to its pre-set position to maintain required flow rates.



S1832



S1832 with Actuator


MATERIALS

No	Part	Material
1	Body	Bronze BS EN 1982 CC491K
2	Bonnet	DZR Brass BS EN 12164 CW602N
3	Stem	Stainless Steel BS EN 10088-3
4	Flow Setting Key	Nylon Grade PA6
5	Fig 631 Pressure Tapping Point	DZR Brass BS EN 12164 CW602N
6	Orifice Insert	DZR Brass BS EN 12164 CW602N
7	Plug	DZR Brass BS EN 12164 CW602N
8	Disc	EPDM WRAS Approved
9	Backing Washer	Stainless Steel BS EN 10088-3
10	O-Ring Retainer	DZR Brass BS EN 12164 CW602N
11	Crane Actuator (Optional Accessory)	N/A

DIMENSIONS, COEFFICIENTS & WEIGHTS

FIG. NO.	NOM. SIZE	DIMENSIONS (MM)			FLOW (Kv)	HEAD LOSS (K)	KVs	WEIGHT (kg)
		A	B	C				
S1832	DN15	87	66	115	1.245	30.27	2.2	0.45
S1832M	DN15	87	66	115	0.667	90.42	1.1	0.45
S1832L	DN15	87	66	115	0.58	325.80	0.58	0.45
S1832	DN20	96	66	115	2.300	34.55	4.7	0.51

DIMENSIONAL DRAWING



PRESSURE/TEMPERATURE RATINGS

The maximum static pressure is 16 bar, the maximum differential pressure is 1.2 bar.

Threaded

TEMPERATURE (°C)	-10 to 100	110	120
PRESSURE (bar)	25	14.8	13.5

Compression

TEMPERATURE (°C)	-10 to 30	65	120
PRESSURE (bar)	16	10	5

Intermediate pressure ratings shall be determined by interpolation

OPERATOR: Motobalance should be fitted with an actuator. Modulating (AM710) and three-point Actuators (A700) are available from Hattersley.

- END CONNECTIONS:**
- Sizes DN15 & DN20 - parallel threaded to BS EN ISO 228-1 (formerly BS 2779).
 - Threaded ANSI is also available. Please add suffix AT to denote American Thread.
 - When using compression adaptors, the maximum pressure must not exceed 16 bar (in line with BS EN 1254/2).



PO BOX 719, IPSWICH, IP1 9UD
HOME SALES: +44 (0)1744 458670
EXPORT SALES: +44 (0)1744 458671
TECHNICAL HELPLINE: 0845 604 1790

FAX: +44 (0)1744 26912
EMAIL: uksales@hattersley.com
EMAIL: export@hattersley.com
www.hattersley.com

Every effort has been made to ensure that the information contained in this publication is accurate at the time of publishing. Crane Ltd assumes no responsibility or liability for typographical errors or omissions or for any misinterpretation of the information within the publication and reserves the right to change without notice.

H_MB_06_2011